

Product data sheet



ePTFE (expanded polytetrafluorethylene) tape

- special sewing thread with excellent UV and weather protection (15 years warranty)
- high tensile strength and abrasion resistance
- unaffected by chlorine bleach and cleaning solutions
- remains flexible even at extreme temperatures or frost
- resists mildew, rot and decay
- resistant against stains



Technical data:

Ticket no.	Col.	Tex no.	correspond. tkt no. of polyester sewing threads	Linear density (dtex) (DIN EN ISO 2060)	Linear density (Nm) (DIN EN ISO 2060)	Breaking force (cN) (DIN EN ISO 2062)	Elongation at break (%) (DIN EN ISO 2062)	Needle size Nm	Needle size no.
HTR	clear	270	20-25	925*3	11/3	8452	10	110-140	18-22
	dyed					6228			
TR	clear	150	35-40	1556*1	6/1	4448	17	100-120	16-19
	dyed					3559			
LTR	clear	110	50-60	1111*1	9/1	3114	17	90-110	14-18

Thermal properties:

- Melting point: 340°C

Article assortment:

Ticket no.	Tex no.	Article no.	Make-up	Spool type	No. of colours
HTR	270	2235	1.050 m	FS	11
TR	150	2203	1.750 m	FS	12
LTR	110	2027	2.100 m	FS	1

Main application:

- Outdoor textiles



Further application:

- Home Interior

Please note: For industrial use only. Not for use in food, drug, cosmetic or medical device manufacturing, processing, or packaging operations.