



AESCULAP® ECONOM II

PROFESSIONAL SHEEP SHEARING MACHINE



TECHNICAL DATA AESCULAP® ECONOM II (GT494)

POWER UNIT	DC motor approx. 2,750 strokes/min
VOLTAGE	230 V / 200 W
NOISE	< 70 dB(A)
WEIGHT	1,200 g
LENGTH OF CABLE	approx. 5 m
SUPPLIED WITH	GT578 upper plate, GT588 lower plate, clipping height 3.5 mm, and solid plastic case including a GT604 Aesculap oiler

FEATURES

- Fast, powerful cutting speed with a high cutting stroke per minute
- Top performance-high powered 200 watt motor
- Considerably improved ventilation with increased aeration vents
- Slim casings and balanced weight for ease of handling
- Built for easy maintenance and repair
 - No tools required to change or clean the filter
 - Easy to change carbon brushes
 - Plug in circuit board
- Internal electronic speed control with overload protection
- Top quality, wear resistant cutting plates for extra life between re-sharpening
- Cutting plates made of special abrasion-resistant steel which can be re-sharpened many times




GT369
shearing head alone, with upper plate GT578, lower plate GT588, can also be connected to cattle clipping machine.



AESCULAP CUTTER PLATES

FOR A SMOOTH AND BEAUTIFUL CUT

Upper Cutter Plate	Lower Cutter Plates	
GT578	GT588 (13 teeth; 3.5 mm)	GT594 (13 teeth; 3.5 mm)
		

AESCULAP® – a B. Braun brand

Aesculap Suhl GmbH | Fröhliche-Mann-Str. 15 | 98528 Suhl | Germany
 clippers@aesculap.de | www.aesculap-clippers.com